


### Alloy Oblong Links

Size (in.)	Working load limit* (lbs.)	Weight each (lbs.)	A	B	C	D	E
3/8	1.13	.75	3.00	2.25	.38	.13	1,800
1/2	1.50	1.00	4.00	3.00	.50	.55	2,900
5/8	1.87	1.25	5.00	3.75	.63	1.10	4,200
3/4	2.25	1.50	6.00	4.50	.75	1.95	6,000
7/8	2.63	1.75	7.00	5.25	.88	2.78	8,300
1	3.00	2.00	8.00	6.00	1.00	4.30	10,800
1-1/4	4.00	2.50	10.25	7.50	1.25	8.50	16,750
1-3/8	4.13	2.75	8.25	8.25	1.38	11.50	20,500



### Eye Hoist Hooks

Rated Capacity tons		Dimensions												
Carbon	Alloy	A	B	C	D	F	G	H	J	K	M	P	Q	AA
3/4	1	4.42	1.47	3.34	2.83	1.25	.73	.81	.90	.63	.56	2.00	.75	1.50
1	1-1/2	5.07	1.75	3.81	3.11	1.38	.84	.94	.93	.71	.63	2.24	.91	2.00
1-1/2	2	5.64	2.13	4.14	3.53	1.50	1.00	1.16	1.00	.99	.75	2.50	1.13	2.00
2	3	6.39	2.41	4.69	3.97	1.63	1.13	1.32	1.13	.94	.85	2.82	1.25	2.00
3	5	7.90	2.94	5.77	4.81	2.00	1.44	1.63	1.47	1.31	1.13	3.51	1.56	2.50
5	7	10.09	3.81	7.37	6.27	2.50	1.81	2.06	1.75	1.66	1.38	4.52	2.00	3.00
7-1/2	11	12.43	4.66	9.07	7.45	3.00	2.25	2.63	2.29	1.88	1.63	5.40	2.44	4.00
10	15	13.94	5.38	10.08	8.30	3.25	2.59	2.94	2.50	2.19	1.94	6.00	2.84	4.00
15	22	17.09	6.63	12.53	10.30	4.25	3.00	3.50	3.50	2.69	2.38	6.93	3.50	5.00