







Type 2 Triangle - Triangle

Nylon or Polyester web slings with alloy steel or alloy aluminum end fittings, for use vertical, choker, and basket hitch applications.



Rated Capacity in Pounds								
Stock #	Width (")	Ply	Vertical	Choker	Basket	60 i	45 i	30 i
								
-1-92	2	1	3,200	2,600	6,400	5,500	4,500	3,200
-2-92	2	2	6,400	5,100	12,800	11,100	9,000	6,400
-1-93	3	1	4,800	3,800	9,600	8,300	6,800	4,800
-2-93	3	2	8,900	7,100	17,800	15,400	12,600	8,900
-1-94	4	1	6,400	5,100	12,800	11,100	9,000	6,400
-2-94	4	2	11,200	9,000	22,400	19,400	15,800	11,200
-1-96	6	1	9,600	7,700	19,200	16,600	13,600	9,600
-2-96	6	2	16,300	13,100	32,600	28,300	23,100	16,300
-1-98	8	1	12,800	10,200	25,600	22,200	18,100	12,800
-2-98	8	2	20,500	16,400	41,000	35,000	29,000	20,500
-1-910	10	1	16,000	12,800	32,000	27,700	22,600	16,000
-2-910	10	2	24,000	19,200	48,000	41,600	33,900	24,000
-1-912	12	1	19,200	15,400	38,400	33,200	27,100	19,200
-2-912	12	2	26,900	21,500	53,700	46,500	38,000	26,900

**Choker rated capacities apply to Type 1 sling only.

Aluminum fittings are used on one-ply slings and steel on 2-ply slings. Steel may be specified on one-ply slings.