















### Single Chain Sling With Master Link and Grab Hook



SOG

Grade 80 Working Load Limits in Pounds								
CHAIN SIZE		SINGLE SLING	DOUBLE SLING			TRIPLE & QUAD SLING		
MM	IN.							
7	9/32	3,500	6,100	4,900	3,500	9,100	7,400	5,200
8	5/16	4,500	7,800	6,400	4,500	11,700	9,500	6,800
10	3/8	7,100	12,300	10,000	7,100	18,400	15,100	10,600
13	1/2	12,000	20,800	17,000	12,000	31,200	25,500	18,000
16	5/8	18,100	31,300	25,600	18,100	47,000	38,400	27,100
20	3/4	28,300	49,000	40,000	28,300	73,500	60,000	42,400
22	7/8	34,200	59,200	48,400	34,200	88,900	72,500	51,300
26	1	47,700	82,600	67,400	47,700	123,900	101,200	71,500
32	1-1/4	72,300	125,200	102,200	72,300	187,800	153,400	108,400

Grade 100 Working Load Limits in Pounds								
CHAIN SIZE		SINGLE SLING	DOUBLE SLING			TRIPLE & QUAD SLING		
MM	IN.							
7	9/32	4,300	7,400	6,100	4,300	11,200	9,100	6,400
8	5/16	5,700	9,900	6,400	5,700	14,800	12,100	7,500
10	3/8	8,800	15,200	12,400	8,800	22,900	18,700	13,200
13	1/2	15,000	26,000	21,200	15,000	32,000	31,800	22,500
16	5/8	22,600	39,100	32,000	22,600	58,700	47,900	33,900
20	3/4	35,300	61,100	49,900	35,300	91,700	74,900	53,000
22	7/8	42,700	74,000	60,400	42,700	110,900	90,600	64,000

Listed Working Load Limits apply only to normal conditions of use in straight configurations with equally loaded legs. For endless slings, WLL's of 75% of above-listed WLL's for the corresponding double leg sling are recommended.