







### Double Chain Sling with Master Link and Sling Hook

Grade 80 Working Load Limits in Pounds				
CHAIN SIZE		DOUBLE SLING		
MM	IN.	 60°	 45°	 30°
7	9/32	6,100	4,900	3,500
8	5/16	7,800	6,400	4,500
10	3/8	12,300	10,000	7,100
13	1/2	20,800	17,000	12,000
16	5/8	31,300	25,600	18,100
20	3/4	49,000	40,000	28,300
22	7/8	59,200	48,400	34,200
26	1	82,600	67,400	47,700
32	1-1/4	25,200	102,200	72,300

Grade 100 Working Load Limits in Pounds				
CHAIN SIZE		DOUBLE SLING		
MM	IN.	 60°	 45°	 30°
7	9/32	7,400	6,100	4,300
8	5/16	9,900	6,400	5,700
10	3/8	15,200	12,400	8,800
13	1/2	26,000	21,200	15,000
16	5/8	39,100	32,000	22,600
20	3/4	61,100	49,900	35,300
22	7/8	74,000	60,400	42,700



DOS

Listed Working Load Limits apply only to normal conditions of use in straight configurations with equally loaded legs. For endless slings, WLL's of 75% of above-listed WLL's for the corresponding double leg sling are recommended.