






## TYPE 315 EIP: Three-Part Braided Sling

Rated Capacity - US Tons



	Rope Dia. (")	Sling Dia. (")	RATED CAPACITY (Tons)			Eye Dimensions (")	
			Vertical	Hitch Choker	Basket	Eye Width	Eye Length
							
6X19 OR 6x36 EIP	1/4	1/2	1.7	1.3	3.4	2	4
	5/16	5/8	2.6	1.9	5.2	3	6
	3/8	3/4	3.6	2.7	7.2	4	8
	7/16	7/8	4.9	3.7	9.8	5	10
	1/2	1	6.4	4.8	12	6	12
	9/16	1 1/8	8	6	16	7	14
	5/8	1 1/4	9.9	7.4	19	8	16
	3/4	1 1/2	14	10	28	10	20
	7/8	1 3/4	19	14	38	12	24
	1	2	24	18	49	14	28
6X36 EIP	1 1/8	2 1/4	31	23	62	16	32
	1 1/4	2 1/2	38	28	76	18	36
	1 3/8	2 3/4	46	34	92	20	40
	1 1/2	3	55	41	110	22	44
	1 3/4	3 1/2	73	54	146	26	52
	2	4	95	71	190	28	56
	2 1/4	4 1/2	118	88	236	32	64
	2 1/2	5	145	109	290	36	72
	2 3/4	5 1/2	173	130	346	40	80
	3	6	204	153	408	44	88
	3 1/2	7	270	202	540	48	96
	4	8	343	257	686	56	112
	4 1/2	9	384	288	768	63	126

Rated Capacities in Basket Hitch based on D/d ratio of 5 times the sling diameter.

Rated capacities based on D/d ratio of 1.5 times the sling diameter inside the eye.

Note: Locked eyes available