









## TYPE 8P1 7X19: Galvanized Braided Sling Rated Capacity - US Tons



	Rope Dia. (")	Sling Dia. (")	Rates Capacity in Tons						Eye Dimensions (")		Slip Thru Thimble	Heavy Thimble
			Vertical 	Choker Hitch 	Basket Hitch 			A	B	ST	HT	
					60 	45 	30 					
<b>7X19 GALV.</b>	1/8	9/16	1.1	1.0	2.2	1.9	1.6	1.1	3	6	ST 10	1/2
	3/16	13/16	1.9	1.6	3.7	3.2	2.6	1.9	4	8	ST 16	5/8
	1/4	1 1/8	3.3	2.9	6.6	5.7	4.7	3.3	5	10	ST 20	7/8
	5/16	1 3/8	5.1	4.5	10	8.9	7.3	5.1	6	12	ST 24	1
	3/8	1 11/16	7.3	6.4	15	13	10	7.3	7	14	ST 36	1 1/8

Made with 7x19 GAC component rope.

Rated Capacities in Basket Hitch based on D/d ratio of 25 times the component rope diameter.

Rated Capacities based on pin diameter no larger than natural eye width or less than the nominal sling diameter.

Rated Capacities based on design factor of 5.

Horizontal sling angles less than 30° shall not be used.

