






TYPE 915 EIP IWRC: Nine-Part Braided Sling

Rated Capacity - US Tons

	Rope Dia. (")	Sling Dia. (")	RATED CAPACITY (Tons)			Eye Dimensions	
			Vertical	Hitch Choker	Hitch Basket	Eye Width (")	Eye Length (")
							
6X19 OR 6X36 EIP	1/4	1	4.3	3.2	8.6	6	12
	5/16	1 1/4	6.6	5	13	6	12
	3/8	1 1/2	9.5	7.1	19	7 1/2	13
	7/16	1 3/4	14	11	29	9	18
	1/2	2	19	14	38	10	20
	9/16	2 3/16	24	18	48	12	24
	5/8	2 1/2	29	22	59	12	24
	3/4	3	42	32	84	15	30
	7/8	3 1/2	57	43	114	17	34
6X36 EIP	1	4	74	56	148	20	40
	1 1/8	4 1/2	93	60	187	22	44
	1 1/4	5	115	86	230	25	50
	1 3/8	5 1/2	138	104	276	27	54
	1 1/2	6	164	123	328	30	60
	1 3/4	7	220	165	440	35	70
	2	8	285	214	570	40	80
	2 1/4	9	355	267	711	45	90
	2 1/2	10	434	326	869	50	100
	2 3/4	11	485	358	970	55	110
	3	12	574	424	1148	60	120
	3 1/2	14	761	563	1421	70	140
4	16	972	719	1544	80	160	
4 1/2	18	1200	888	2400	90	180	



Rated Capacities based on pin diameter no larger than natural width or less than the nominal diameter
 Rated Capacities in basket hitch based on D/d ratio of 5 times the sling body diameter
 Rated Capacities based on design factor of 5.
 Horizontal sling angles of less than 30° shall not be used.