









## TYPE CL15: Galvanized Cable Laid Single Part Sling Rated Capacity - US Tons



Rope Dia. (")	Vertical	Choker Hitch	Basket Hitch			Eye Dimensions (")		Thimble Dimensions		Alloy Hook		
							A	B	A	B	WLL Tons	
				60°	45°	30°						
7X7X7	1/4	0.50	0.34	1.0	0.87	0.71	0.50	2.0	4	0.88	1.63	1
	3/8	1.1	0.74	2.2	1.9	1.5	1.1	3.0	6	1.13	2.13	1 1/2
	1/2	1.9	1.3	3.7	3.2	2.6	1.9	4.0	8	1.5	2.75	2
	5/8	2.8	1.9	5.5	4.8	3.9	2.8	5.0	10	1.75	3.25	3
7X7X19	3/4	4.1	2.8	8.1	7.0	5.8	4.1	6.0	12	2.0	3.75	5
	7/8	5.4	3.7	11	9.4	7.6	5.4	7.0	14	2.25	4.25	7
	1	6.9	4.7	14	12	9.7	6.9	8.0	16	2.5	4.50	7
	1 1/8	8.3	5.8	17	14	12	8.3	9.0	18	2.88	5.13	11
	1 1/4	9.9	7.0	20	17	14	9.9	10	20	2.88	5.13	11

Rated Capacities Basket Hitch based on D/d ratio of 25 times the component rope diameter.

Rated Capacities based on pin diameter no larger than natural eye width or less than the nominal sling diameter.

Rated Capacities based on design factor of 5.

Horizontal sling angles less than 30° shall not be used.