




Type 10 Multi-Leg Bridles

Nylon or Polyester bridle assemblies are useful whenever the load is equipped with permanent lifting attachments. For such applications, bridle assemblies are lightweight, easy to use, and economical.



Rated Capacity in Pounds										
Stock #	Width (")	Ply	Rated capacity			pear link (p)	Alloy Oblong Hook (O)	Hoist hook ()	Fabric Eye Dimensions	
			60 i	45 i	30 i				L	W
						Size	Size	Size (WLL)		
-1-91	1	1	2,800	2,300	1,600	1/2	1/2	1	9	1
-2-91	1	2	5,500	4,500	3,200	3/4	5/8	2	9	1
-1-92	2	1	5,500	4,500	3,200	3/4	5/8	2	9	2
-2-92	2	2	11,100	9,000	6,400	1	1	5	9	2
-1-93	3	1	8,300	6,800	4,800	7/8	3/4	3	12	1 1/2
-2-93	3	2	15,400	12,500	8,900	1 1/4	1	5	12	1 1/2

* Use prefix E for Eye, SH for safety Hook.

Assemblies of one, three, or four legs are available upon special request. Additional end fittings can also be supplied.

Ordering Multi-Leg Bridles

A.- Choose the stock number you need from the chart.

B.- Choose the end attachments you need, using the code letters shown above. Insert these letters as a prefix for your stock number in this sequence:

1.- The link attachment: P (pear-shaped) or O (oblong)

2.- The end attachment: SH (safety hook), E (sewn eye), P (pear-shaped), O (oblong). For each leg you need use a letter to designate the end attachment.

Example: an "OEEE" is a three-leg assembly with an allow oblong (O) as link attachment and a sew eye (E) as the end attachment for each of the three legs.

3.- Choose the length you need and add it at the end of the stock number.

Example: An OSHSH-1-92 x 10' is a two-leg assembly with an alloy oblong link as link attachment and a safety hook (SH) as the end attachment for each of the two legs. A "1-92" stock number represents a two-inch wide, one-ply sling.

The length is 10 feet.