

Aluminum Triangles										
Size	A	B	C	D	E	F	G	Approx. weight in lbs.	Rated capacity in lbs.	Min. break
T2	4	3 5/8	2 1/4	1 3/4	15/16	2 3/8	9/16	0.31	3,360	16,800
T3	5 1/4	5	3 1/4	2	1 3/16	3 5/16	5/8	0.75	5,000	25,000
T4	6 1/4	6 5/8	4 3/8	2 3/8	1 7/16	4	11/16	1.10	6,700	33,500
T6	8 5/16	8 7/8	6 3/8	3 1/8	1 3/4	5 1/2	15/16	2.70	9,700	48,500

Aluminum Chokers										
Size	A	B	C	D	E	F	G	Approx. weight in lbs.	Rated capacity in lbs.	Min. break
C2	6 1/8	5 1/4	2 1/8	1 3/4	15/16	2 3/8	9/16	0.73	3,360	16,800
C3	7 1/2	7 1/8	3 1/8	2	1 1/8	3 5/16	5/8	1.30	5,000	25,000
C4	8 3/4	9 3/4	4 1/8	2 3/8	1 7/16	4	11/16	1.90	6,700	33,500
C6	11 5/16	11 3/4	6 1/8	3 1/8	1 3/4	5 1/2	15/16	5.10	9,700	48,500