

SYNTHETIC SLINGS WEB SLINGS



TYPE 5 ENDLESS







Nylon or polyester endless web slings, for use in vertical, choker, and basket hitch applications.



WARNING



See page 12-14 for inspection and removal criteria

Stock #	Width (")	Ply	Vert 	Choker Hitch 		Basket Hitch		
						Degrees		
						60° 	45° 	30° 
EN-1-91	1	1	3,200	2,550	6,400	5,500	4,500	3,200
EN-2-91	1	2	6,200	4,950	12,400	10,700	8,750	6,200
EN-3-91	1	3	8,200	6,600	16,400	14,100	11,550	8,200
EN-4-91	1	4	11,000	8,800	22,000	19,050	15,550	11,000
EN-1-92	2	1	6,200	4,950	12,400	10,700	8,750	6,200
EN-2-92	2	2	12,400	9,900	24,800	21,450	17,500	12,400
EN-3-92	2	3	16,500	13,200	33,000	28,350	23,250	16,500
EN-4-92	2	4	22,000	17,600	44,000	38,100	31,100	22,000
EN-1-93	3	1	9,400	7,500	18,800	16,250	13,250	9,400
EN-2-93	3	2	17,600	14,050	35,200	30,450	24,850	17,600
EN-3-93	3	3	24,700	19,800	49,400	42,450	34,800	24,700
EN-4-93	3	4	32,900	26,300	65,800	56,950	46,500	32,900
EN-1-94	4	1	12,400	9,900	24,800	21,450	17,500	12,400
EN-2-94	4	2	22,000	17,600	44,000	38,100	31,100	22,000
EN-3-94	4	3	30,600	24,500	61,200	52,600	43,100	30,600
EN-4-94	4	4	40,800	32,600	81,600	70,650	57,700	40,800
EN-1-96	6	1	18,600	14,850	37,200	32,200	26,300	18,600
EN-2-96	6	2	33,000	26,400	66,000	57,150	46,650	33,000
EN-3-96	6	3	45,900	36,700	91,800	78,900	64,700	45,900
EN-4-96	6	4	61,200	48,950	122,400	106,000	86,550	61,200
EN-1-98	8	1	21,200	16,950	42,400	36,700	29,950	21,200
EN-2-98	8	2	42,300	33,800	84,600	73,250	59,800	42,300
EN-3-98	8	3	61,400	49,100	122,800	105,600	86,550	61,400
EN-4-98	8	4	81,900	65,500	163,800	140,900	115,500	81,900
EN-1-910	10	1	26,500	21,200	53,000	45,850	37,450	26,500
EN-2-910	10	2	52,900	42,300	105,800	91,600	74,800	52,900
EN-3-910	10	3	72,000	57,600	144,000	124,650	101,800	72,000
EN-4-910	10	4	96,000	76,800	192,000	165,100	135,350	96,000
EN-1-912	12	1	31,800	25,400	63,600	55,050	44,950	31,800
EN-2-912	12	2	63,500	50,800	127,000	109,950	89,800	63,500
EN-3-912	12	3	80,000	64,000	160,000	138,550	113,100	80,000
EN-4-912	12	4	107,000	86,000	214,000	184,900	151,300	107,000



Rated capacities are in pounds. Consider using round slings in applications requiring 3- and 4-ply slings wider than 4". End tapering available in 1- and 2-ply slings 2" - 12"