

TYPE 3 EYE & EYE FLAT

Nylon or polyester web slings, for use in vertical, choker, and basket hitch applications.

TYPE 4 EYE & EYE TWIST

WARNING

See page 12-14 for inspection and removal criteria

Stock # *	Width (")	Ply	Vert	Choker Hitch	Basket Hitch				Eye Length (")	Eye Width (")
					Degrees					
					60°	45°	30°			
-1-91	1	1	1,600	1,250	3,200	2,750	2,250	1,600	9	1
-2-91	1	2	3,100	2,450	6,200	5,350	4,350	3,100	9	1
-3-91	1	3	4,100	3,300	8,200	7,050	5,750	4,100	12	1
-4-91	1	4	5,500	4,400	11,000	9,500	7,750	5,500	12	1
-1-92	2	1	3,100	2,450	6,200	5,350	4,350	3,100	12	2
-2-92	2	2	6,200	4,950	12,400	10,700	8,750	6,200	12	2
-3-92	2	3	8,200	6,600	16,400	14,100	11,550	8,200	12	2
-4-92	2	4	11,000	8,800	22,000	19,050	15,550	11,000	12	2
-1-93	3	1	4,700	3,750	9,400	8,100	6,600	4,700	12	1-1/2
-2-93	3	2	8,800	7,000	17,600	15,200	12,400	8,800	12	1-1/2
-3-93	3	3	12,300	9,900	24,600	21,150	17,300	12,300	18	1-1/2
-4-93	3	4	16,400	13,100	32,800	28,400	23,150	16,400	18	1-1/2
-1-94	4	1	6,200	4,950	12,400	10,700	8,750	6,200	14	2
-2-94	4	2	11,000	8,800	22,000	19,050	15,550	11,000	14	2
-3-94	4	3	15,300	12,200	30,600	26,300	21,550	15,300	18	2
-4-94	4	4	20,400	16,300	40,800	35,300	28,850	20,400	18	2
-1-96	6	1	9,300	7,400	18,600	16,100	13,150	9,300	24	2
-2-96	6	2	16,500	13,200	33,000	28,550	23,300	16,500	24	2
-3-96	6	3	22,900	18,300	45,800	39,300	32,250	22,900	24	3
-4-96	6	4	30,600	24,450	61,200	53,000	43,250	30,600	24	3
-1-98	8	1	11,800	9,400	23,600	20,400	16,650	11,800	24	3
-2-98	8	2	22,700	18,150	45,400	39,300	32,100	22,700	24	3
-3-98	8	3	30,700	24,600	61,400	52,800	43,250	30,700	24	4
-4-98	8	4	40,900	32,750	81,800	70,450	57,750	40,900	24	4
-1-910	10	1	14,700	11,750	29,400	25,450	20,750	14,700	24	4
-2-910	10	2	28,400	22,700	56,800	49,150	40,150	28,400	24	4
-3-910	10	3	36,000	28,800	72,000	61,900	50,750	36,000	30	5
-4-910	10	4	48,000	38,400	96,000	82,550	67,650	48,000	30	5
-1-912	12	1	17,600	14,050	35,200	30,450	24,850	17,600	30	5
-2-912	12	2	34,100	27,250	68,200	59,050	48,200	34,100	30	5
-3-912	12	3	40,300	32,200	80,600	69,300	56,800	40,300	36	6
-4-912	12	4	53,700	43,000	107,400	92,450	75,800	53,700	36	6



*Use prefix "EET" for Twist Eye and "EEF" for Flat Eye stock numbers. Rated capacities are in pounds. Consider using round slings in applications requiring 3- and 4-ply slings wider than 6".