



**TYPE 1 TRIANGLE  
TRIANGLE & CHOKER**

Nylon or polyester web slings, for use in vertical, choker, and basket hitch applications.

**TYPE 2 TRIANGLE  
TRIANGLE & TRIANGLE**



Stock # *	Width (")	Ply	Vertical	Choker	Basket	60°	45°	30°
-1-92	2	1	3,100	2,450	6,200	5,350	4,350	3,100
-2-92	2	2	6,200	4,950	12,400	10,700	8,750	6,200
-1-93	3	1	4,700	3,750	9,400	8,100	6,600	4,700
-2-93	3	2	8,800	7,000	17,600	15,200	12,400	8,800
-1-94	4	1	6,200	4,950	12,400	10,700	8,750	6,200
-2-94	4	2	11,000	8,800	22,000	19,050	15,550	11,000
-1-96	6	1	9,300	7,400	18,600	16,100	13,150	9,300
-2-96	6	2	16,500	13,200	33,000	28,550	23,300	16,500
-2-98	8	2	22,400	17,900	44,800	38,750	31,650	22,400
-2-910	10	2	28,000	22,400	56,000	48,450	39,600	28,000
-2-912	12	2	32,000	27,250	64,000	55,400	45,250	32,000



*Rated capacities are in pounds. Choker rated capacities apply to Type 2 slings only. Type 1 slings are not to be used in a choker hitch.*

Aluminum fittings are used on 1-ply slings (2", 4", and 6" wide webbing only) and steel on 2-ply slings. Steel may be specified on 1-ply slings.

\*Stock # prefixes:

- TCA - Type 1 - aluminum fittings
- TCS - Type 1 - steel fittings
- TTA - Type 2 - aluminum fittings
- TTS - Type 2 - steel fittings

**WARNING**

See page 12-14 for inspection and removal criteria

**WARNING:**

Never use aluminum fittings where fumes, vapors, mists or liquids of caustics are present. Aluminum fittings are degraded by salt water and should not be cleaned with chlorine based solutions.